



D-SERIES SMART SELECTION GUIDE

SMART.

The intelligent choice



Application	Residential	Light Industrial	Light Industrial	Industrial	Industrial	Industrial
Maximum Gate Weight	300kg	500kg	600kg	1000kg	250kg	2000kg
Operator Maximum Speed	24m/min	24m/min	36m/min	26m/min	43m/min	18m/min
Maximum Push Force (running)	12kgf	17kgf	17kgf	30kgf	18kgf	39kgf
Maximum Push Force (start)	18kgf	30kgf	30kgf	40kgf	24kgf	52kgf
Operator Voltage	12V	12V	24V	24V	24V	24V
Compatible with the Power Pack	-	-	✓	✓	✓	✓
Input (I) Low Current Output (LCO) High Current Output (HCO)	2x I	3x I 2x LCO 1x HCO	4x I/LCO 2x I/HCO	4x I/LCO 2x I/HCO	4x I/LCO 2x I/HCO	4x I/LCO 2x I/HCO
Onboard Tamper Alarm	-	✓	✓	✓	✓	✓
Engineered Product Life (cycles)	75k	150k	200k	250k	250k	250k
Maximum Auxillary Supply	12VDC @ 300mA	12VDC @ 3A	24VDC @ 3A	24VDC @ 3A	24VDC @ 3A	24VDC @ 3A
NOVA Receiver Storage Capacity	32	1500	1500	1500	1500	1500
MyCentsys Remote						
- User Capacity	32	1500	1500	1500	1500	1500
- Visitors Access Sharing Users	10	10	10	10	10	10
MyCentsys Pro						
- Admin Users	10	10	10	10	10	10



SCAN THIS QR CODE
TO DOWNLOAD OUR MOBILE
APPLICATIONS
AND GET THE ULTIMATE
SMART EXPERIENCE

